

The Linux 2.4 Kernel's Startup Procedure

Table of Contents

[Overview](#)

[The Big Picture](#)

[In The Beginning...](#)

[The `_stext` Function](#)

[The `start_kernel\(\)` Function](#)

[The `setup_arch\(\)` Function](#)

[The `trap_init\(\)` Function](#)

[The `init_IRQ\(\)` Function](#)

[The `sched_init\(\)` Function](#)

[The `softirq_init\(\)` Function](#)

[The `time_init\(\)` Function](#)

[The `console_init\(\)` Function](#)

[The `init_modules\(\)` Function](#)

[The `kmem_cache_init\(\)` Function](#)

[The `calibrate_delay\(\)` Function](#)

[The `mem_init\(\)` Function](#)

[The `kmem_cache_sizes_init\(\)` Function](#)

[The `fork_init\(\)` Function](#)

[The `proc_caches_init\(\)` Function](#)

[The `vfs_caches_init\(\)` Function](#)

[The `buffer_init\(\)` Function](#)

[The `page_cache_init\(\)` Function](#)

[The `signals_init\(\)` Function](#)

[The `proc_root_init\(\)` Function](#)

[The `ipc_init\(\)` Function](#)

[The `check_bugs\(\)` Function](#)

[The `smp_init\(\)` Function](#)

[The `rest_init\(\)` Function](#)

[The `init\(\)` Function](#)

[The `do_initcalls\(\)` Function](#)

[The `mount_root\(\)` Function](#)

[The `/sbin/init` Program](#)

[Conclusion](#)

[Copyright](#)

[About the Author](#)

Overview

This paper describes the Linux 2.4 kernel's startup process, from the moment the kernel gets control of the host hardware until the kernel is ready to run user processes. Along the way, it covers the programming environment Linux expects at boot time, how peripherals are initialized, and how Linux knows what to do next.

[Next >>>](#)

The Big Picture

[<<<](#)[Previous](#)[Next >>>](#)

The Big Picture

[Figure 1](#) is a function call diagram that describes the kernel's startup procedure. As it shows, kernel initialization proceeds through a number of distinct phases, starting with basic hardware initialization and ending with the kernel's launching of `/bin/init` and other user programs. The dashed line in the figure shows that `init()` is invoked as a kernel thread, not as a function call.



Figure 1. The kernel's startup procedure.

[Figure 2](#) is a flowchart that provides an even more generalized picture of the boot process, starting with the bootloader extracting and running the kernel image, and ending with running user programs.



Figure 2. The kernel's startup procedure, in less detail.

The following sections describe each of these function calls, including examples taken from the Hitachi SH7750/Sega Dreamcast version of the kernel.

[<<< Previous](#)[Home](#)[Next >>>](#)

In The Beginning...

In The Beginning...

The Linux boot process begins with the kernel's `_stext` function, located in `arch/<host>/kernel/head.S`. This function is called `_start` in some versions. Interrupts are disabled at this point, and only minimal memory accesses may be possible depending on the capabilities of the host hardware.

The code to invoke `_stext` is found in the host's bootloader, code that is technically not part of Linux itself. In most kernel implementations the bootloader is a standalone program that drags the kernel image from the storage media (flash memory, hard disk, floppy, CD, etc.) into RAM, decompresses it, and jumps to `_stext`.

The bootloader extracts the compressed kernel image to a predefined location that is appropriate for the target architecture; `_stext` is, by convention, located 0x1000 bytes after the beginning of the image.

In the Hitachi SH Linux kernel, the linker places the start of the kernel image at the address 0x80000000 and defines a symbol called `_text` there. Once the kernel image is decompressed, the bootloader jumps to the address (`_text + 0x1000`). [Figure 3](#) shows the relevant portions of the bootloader's command file and startup code. The excerpts shown are taken from `arch/sh/vmlinux.lds.S` and `arch/sh/boot/compressed/head.S`.

```
/* linker configuration script */
SECTIONS
{
    . = 0x80000000 + CONFIG_MEMORY_START + 0x1000;
    _text = .;                /* Text and read-only data */
    ...
}

/* bootloader code */
startup:
    ...

/* Jump to the start of the decompressed kernel */
mov.l    kernel_start_addr, r0
jmp      @r0
```

```
    nop
kernel_start_addr:
    .long    _text+0x1000
```

Figure 3. The Hitachi SH kernel's linker configuration script and bootloader code.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The Big Picture

The `_stext` Function

The _stext Function

The function `_stext` (called `_start` in some versions) is usually located in `arch/<host>/kernel/head.S`.

`_stext` sets the initial stack pointer and performs any other functions necessary to create a minimal C runtime environment, like clearing the BSS memory section. `_stext` then jumps to `start_kernel()`.

[Figure 4](#) shows part of the code for the Hitachi SH version of `_stext`.

```
ENTRY(_stext)
!   Initialize Status Register
mov.l 1f, r0      ! MD=1, RB=0, BL=0, IMASK=0xF
ldc  r0, sr
!   Initialize global interrupt mask
mov  #0, r0
ldc  r0, r6_bank
!
mov.l 2f, r0
mov  r0, r15     ! Set initial r15 (stack pointer)
mov  #0x20, r1   !
shll8 r1        ! r1 = 8192
sub  r1, r0
ldc  r0, r7_bank ! ... and init_task

!   Initialize fpu
mov.l 7f, r0
jsr  @r0
nop

!   Enable cache
mov.l 6f, r0
jsr  @r0
nop

!   Clear BSS area
mov.l 3f, r1
add  #4, r1
mov.l 4f, r2
mov  #0, r0
9:  cmp/hs      r2, r1
```

```
bf/s 9b ! while (r1 < r2)
mov.l r0,@-r2
! Start kernel
mov.l 5f, r0
jmp @r0
nop

        .balign 4
1:      .long 0x400000F0          ! MD=1, RB=0, BL=0, FD=0, IMASK=0xF
2:      .long SYMBOL_NAME(stack)
3:      .long SYMBOL_NAME(__bss_start)
4:      .long SYMBOL_NAME(_end)
5:      .long SYMBOL_NAME(start_kernel)
6:      .long SYMBOL_NAME(cache_init)
7:      .long SYMBOL_NAME(fpu_init)
```

Figure 4. The Hitachi SH's _stext function.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

In The Beginning...

The start_kernel() Function

The start_kernel() Function

start_kernel() is located in kernel/init/main.c.

The start_kernel() function orchestrates all of Linux's startup procedure. Prior to invoking all the other functions needed to get the kernel into an operational state, start_kernel() prints the familiar Linux startup banner and parses the command line.

The following sections describe each of the functions called by start_kernel(), in the order of their invocation. The code in [Figure 5](#) shows the first few lines of start_kernel().

```
asmlinkage void __init start_kernel(void)
{
    char * command_line;
    unsigned long mempages;
    extern char saved_command_line[];

    lock_kernel();
    printk(linux_banner);
    setup_arch(&command_line);
    printk("Kernel command line: %s\n", saved_command_line);
    parse_options(command_line);
    trap_init();
    init_IRQ();
    ...
}
```

Figure 5. The start_kernel() function.

[<<<](#)[Previous](#)[Next >>>](#)

The setup_arch() Function

Setup_arch() is usually located in arch/<host>/kernel/setup.c.

The setup_arch() function is responsible for initial, machine-specific initialization procedures. These include setting up the *machine vector* for the host, and determining the locations and sizes of available memory. Setup_arch() also initializes a basic memory allocator called *bootmem* to use during the boot process, and for most processors, calls paging_init() to enable the host's Memory Management Unit (MMU).

The host's *machine vector* is a data structure containing the name of the host, and function pointers for host-specific functions to read and write i/o ports. The machine vector reduces the number of configuration points in the kernel, by allowing host-specific operations in generic kernel code to use a common API.

[<<< Previous](#)[Home](#)[Next >>>](#)

The start_kernel()
Function

The trap_init() Function

The trap_init() Function

Trap_init() is usually located in arch/<host>/kernel/traps.c.

Trap_init() initializes some of the processor's interrupt handling capability. In particular, it aims the processors interrupt vector table pointer to the address of the actual vector table, if necessary. Interrupts are not enabled until later on, just before the calibrate_delay() function is run.

The code in [Figure 6](#) shows trap_init() for the Hitachi SH.

```
void __init trap_init(void)
{
    extern void *vbr_base;
    extern void *exception_handling_table[14];

    exception_handling_table[12] = (void *)do_reserved_inst;
    exception_handling_table[13] = (void *)do_illegal_slot_inst;

    asm volatile("ldc  %0, vbr"
                 : /* no output */
                 : "r" (&vbr_base)
                 : "memory");
}
```

Figure 6. The trap_init() function.

[<<<](#)[Previous](#)[Next >>>](#)

The `init_IRQ()` Function

`init_IRQ()` is usually located in `arch/<host>/kernel/irq.c`. The Hitachi SH version is in `arch/<host>/kernel/irq_ipr.c`.

`init_IRQ()` initializes the hardware-specific side of the kernel's interrupt subsystem. Interrupt controllers are initialized here, but their input lines are not enabled until drivers and kernel modules call `request_irq()`.

[<<< Previous](#)[Home](#)[Next >>>](#)The `trap_init()` FunctionThe `sched_init()` Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The sched_init() Function

Sched_init() is located in kernel/sched.c.

Sched_init() initializes the kernel's pidhash[] table, a lookup table for quickly mapping process IDs to process descriptors used by the kernel. The sched_init() function then initializes the vectors and bottom-half handlers used by the kernel's various internal timers.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The init_IRQ() Function

The softirq_init()
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `softirq_init()` Function

`Softirq_init()` is located in `kernel/softirq.c`.

`Softirq_init()` initializes the kernel's *softirq* subsystem. Softirqs are the 2.4 kernel's replacement for bottom-half handlers used in version 2.2.x, and are used to improve interrupt handling performance for things like network packet transmission and reception.

Softirqs are managed by the kernel's **ksoftirqd** thread.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `sched_init()` Function

The `time_init()` Function

The time_init() Function

time_init() is usually located in arch/<host>/kernel/time.c.

The time_init() function initializes the host's system tick timer hardware. It installs the timer's interrupt handler, and configures the timer to produce a periodic tick. The tick interrupt handler is usually called do_timer_interrupt().

A portion of the Hitachi SH version of time_init() is shown in [Figure 7](#). The timer interrupt handler timer_interrupt() (which calls do_timer_interrupt()) is installed, then after determining the proper clock frequency (not shown), the code starts the chip's TMU0 periodic timer.

```
static struct irqaction irq0 = {timer_interrupt, SA_INTERRUPT, 0,
                                "timer", NULL, NULL};

void __init time_init(void)
{
    unsigned long interval;

    ...

    setup_irq(TIMER_IRQ, &irq0);

    ...

    interval = (module_clock/4 + HZ/2) / HZ;
    printk("Interval = %ld\n", interval);

    ...

    /* Start TMU0 */
    ctrl_outb(0, TMU_TSTR);
    ctrl_outb(TMU_TOCR_INIT, TMU_TOCR);
    ctrl_outw(TMU0_TCR_INIT, TMU0_TCR);
    ctrl_outl(interval, TMU0_TCOR);
    ctrl_outl(interval, TMU0_TCNT);
    ctrl_outb(TMU_TSTR_INIT, TMU_TSTR);
}
```

Figure 7. An excerpt from the Hitachi SH's time_init() function.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The softirq_init()
Function

The console_init()
Function

[<<<](#)[Previous](#)[Next >>>](#)

The console_init() Function

Console_init() is located in `drivers/char/tty_io.c`.

The `console_init()` function performs early initialization of the kernel's serial console device, if one is configured for use. This console device is used to display kernel boot messages before the formal, complete virtual console system is initialized.

Once some basic TTY information is recorded, `console_init()` calls a host-specific console initialization function like `sci_console_init()`, which uses the Hitachi SH's SCI peripheral as a serial console.

In most cases, the kernel's console device is the host's VGA display hardware, or a serial port. By creating your own terminal initialization function for `console_init()`, however, just about any primitive interface is possible. Consoles that talk to network hosts can't be used here, since the kernel's networking subsystem has not yet been initialized.

[<<< Previous](#)[Home](#)[Next >>>](#)The `time_init()` FunctionThe `init_modules()`
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `init_modules()` Function

`init_modules()` is located in `kernel/module.c`.

The `init_modules()` function initializes the kernel module subsystem's `nsyms` parameter.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `console_init()`
Function

The `kmem_cache_init()`
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `kmem_cache_init()` Function

`kmem_cache_init()` is located in `mm/slab.c`. This function initializes the kernel's SLAB memory management subsystem. SLABs are used for dynamic memory management of internal kernel structures.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `init_modules()`
Function

The `calibrate_delay()`
Function

[<<<](#)[Previous](#)[Next >>>](#)

The calibrate_delay() Function

Calibrate_delay() is located in `init/main.c`.

The `calibrate_delay()` function performs the kernel's infamous *BogoMips(tm)* calculation. A *BogoMip* is a unitless number that calibrates Linux's internal delay loops, so that delays run at roughly the same rate on processors of different speeds.

The BogoMips calculation depends on the value of `jiffies`, the number of timer ticks since system startup. If the system tick is not working, the BogoMips calculation will freeze.

[<<< Previous](#)[Home](#)[Next >>>](#)

The `kmem_cache_init()`
Function

The `mem_init()` Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `mem_init()` Function

`Mem_init()` is located in `arch/<host>/mm/init.c`.

`Mem_init()` initializes the kernel's memory management subsystem. It also prints a tabulation of all available memory and the memory occupied by the kernel.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `calibrate_delay()`
Function

The
`kmem_cache_sizes_init()`
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `kmem_cache_sizes_init()` Function

`kmem_cache_sizes_init()` is located in `mm/slab.c`.

The `kmem_cache_sizes_init()` function finishes the SLAB subsystem initialization started by `kmem_cache_init()`.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `mem_init()` Function

The `fork_init()` Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The fork_init() Function

Fork_init() is located in kernel/fork.c.

Fork_init() initializes the kernel's max_threads and init_task variables. This information is used by the kernel during fork() system calls.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The
kmem_cache_sizes_init()
Function

The proc_caches_init()
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `proc_caches_init()` Function

`Proc_caches_init()` is located in `kernel/fork.c`.

`Proc_caches_init()` initializes the SLAB caches used by the kernel. This is analogous to initializing `malloc()`-style heaps in a user program.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `fork_init()` Function

The `vfs_caches_init()`
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `vfs_caches_init()` Function

`vfs_caches_init()` function is located in `fs/dcache.c`.

`vfs_caches_init()` initializes the SLAB caches used by the kernel's Virtual File System subsystem.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `proc_caches_init()`
Function

The `buffer_init()` Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `buffer_init()` Function

`buffer_init()` is located in `fs/buffer.c`.

`buffer_init()` initializes the kernel's buffer cache hash table. The buffer cache holds blocks of adjacent disk data, and is used to improve the performance of reads and writes to hard disks and other slow media.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `vfs_caches_init()`
Function

The `page_cache_init()`
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The page_cache_init() Function

Page_cache_init() function is located in mm/filemap.c.

Page_cache_init() initializes the kernel's page cache subsystem. Page caches hold streams of file data, and help improve performance when reading and writing user files.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The buffer_init() Function

The signals_init()
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `signals_init()` Function

`signals_init()` is located in `kernel/signal.c`.

`signals_init()` initializes the kernel's signal queue. Signals are a form of interprocess communication.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `page_cache_init()`
Function

The `proc_root_init()`
Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `proc_root_init()` Function

`Proc_root_init()` is located in `fs/proc/root.c`.

`Proc_root_init()` initializes Linux's `/proc` filesystem, and creates several standard entries like `/proc/bus` and `/proc/driver`.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `signals_init()`
Function

The `ipc_init()` Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `ipc_init()` Function

`ipc_init()` is located in `ipc/util.c`.

`ipc_init()` initializes the resources that implement SystemV-style interprocess communication, including semaphores (initialized in the subfunction `sem_init()`), messages (`msg_init()`) and shared memory (`shm_init()`).

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `proc_root_init()`
Function

The `check_bugs()` Function

[<<<](#)[Previous](#)[Next >>>](#)

The check_bugs () Function

check_bugs () is located somewhere in the host-specific portions of the kernel source tree. For some versions, it is declared in `include/asm-<host>/bugs.h`, so that it can be statically included in `start_kernel ()`.

The `check_bugs ()` function is where host-specific code can check for known processor errata, and implement workarounds if possible. Some implementations of this function check for FPU bugs, opcodes that are not supported by the whole processor family, and buggy opcodes.

check_bugs () also usually calls `identify_cpu ()`, to detect which version of a processor family is in use. For example, the x86 kernel's `identify_cpu ()` can identify and apply runtime fixes for Coppermine, Celeron, and Pentium Pro/II/III processors, as well as chips from non-Intel vendors like AMD and Transmeta.

[<<< Previous](#)[Home](#)[Next >>>](#)The `ipc_init ()` FunctionThe `smp_init ()` Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The `smp_init()` Function

`smp_init()` is defined in `init/main.c`.

If the host machine is an SMP-capable x86 processor, `smp_init()` calls `IO_APIC_init_uniprocessor()` to set up the processor's APIC peripheral. For other processor families, `smp_init()` is defined as a do-nothing.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `check_bugs()` Function

The `rest_init()` Function

[<<<](#)

[Previous](#)

[Next >>>](#)

The rest_init() Function

Rest_init() is located in `init/main.c`.

Rest_init() frees the memory used by initialization functions, then launches `init()` as a kernel thread to finish the kernel's boot process.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `smp_init()` Function

The `init()` Function

The `init()` Function

`init()` is located in `init/main.c`.

`init()` completes the kernel's boot process by calling `do_basic_setup()` to initialize the kernel's PCI and network features. The remaining memory allocated for initialization is discarded, scheduling is enabled, the standard input, output and error streams are created, and `prepare_namespace()` is called to mount the root filesystem.

With the root filesystem in place, `init()` runs `execve()` to launch the program `/sbin/init`, if it exists. If a valid program name is provided with the `init=<programname>` command line option, `init()` will `execve()` that program instead. If a suitable startup program cannot be found (the kernel also tries `/bin/init` and `/bin/sh`), the kernel panics and halts.

The code for `init()` is shown in [Figure 8](#).

```
static int init(void * unused)
{
    lock_kernel();
    do_basic_setup();

    prepare_namespace();

    free_initmem();
    unlock_kernel();

    if (open("/dev/console", O_RDWR, 0) < 0)
        printk("Warning: unable to open an initial console.\n");

    (void) dup(0);
    (void) dup(0);

    if (execute_command) execve(execute_command, argv_init, envp_init);
    execve("/sbin/init", argv_init, envp_init);
    execve("/bin/init", argv_init, envp_init);
    execve("/bin/sh", argv_init, envp_init);
    panic("No init found. Try passing init= option to kernel.");
}
```

```
}
```

Figure 8. The `init()` function.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `rest_init()` Function

The `do_initcalls()`
Function

The do_initcalls() Function

do_initcalls() is located in `init/main.c`.

do_initcalls() runs the list of functions registered with the `__initcall` attribute, which usually only applies to compiled-in kernel modules and device drivers. The `__initcall` attribute eliminates the need for a hand-maintained list of device driver initialization functions.

The `__initcall` mechanism works by creating a constant function pointer in a memory section called `.initcall.init`, that points to the initialization function itself. When the kernel image is linked, the linker organizes all of these function pointers into a single memory section, and `do_initcalls()` invokes them in the order they appear there.

The macros and type definitions that implement the `__initcall` attribute are shown in [Figure 9](#); the code for `do_initcalls()` is shown in [Figure 10](#).

```
typedef int (*initcall_t)(void);
typedef void (*exitcall_t)(void);

#define __initcall(fn) \
    static initcall_t __initcall_##fn __init_call = fn

#define __init_call __attribute__((unused,__section__ (".initcall.init")))
```

Figure 9. The `__initcall` macros and typedefs.

```
extern initcall_t __initcall_start, __initcall_end;

static void __init do_initcalls(void)
{
    initcall_t *call;

    call = &__initcall_start;
    do {
        (*call)();
        call++;
    } while (call < &__initcall_end);

    flush_scheduled_tasks();
}
```

```
}
```

Figure 10. The do_initcalls() function.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The init() Function

The mount_root() Function

[<<<](#)[Previous](#)[Next >>>](#)

The mount_root () Function

Mount_root () is located in fs/super.c.

Mount_root () tries to mount the root filesystem. The identity of the root filesystem is provided as a kernel option during boot, which in workstation environments is typically the hard disk device and partition containing the system's root directory. (The root partition isn't necessarily the same as the location of the now almost-booted kernel image.)

Linux can mount root filesystems from hard disks, floppies, and over a network NFS connection to another machine. Linux can also use a *ramdisk* as a root filesystem. Mount_root () will try one or more of these sources before giving up and causing a kernel panic.

[<<< Previous](#)[Home](#)[Next >>>](#)

The do_initcalls()
Function

The /sbin/init Program

The /sbin/init Program

The program `/sbin/init` (hereafter called just **init**) is the parent of all user processes. **Init**'s job is to create other user processes by following the instructions found in the file `/etc/inittab`. Technically, the kernel itself has completely booted before **init** runs--- it has to, since **init** is a user process. Despite this, most consider **init** to be "part of the boot process".

The `inittab` script usually has entries to tell **init** to run programs like **mingetty** that provide login prompts, and to run scripts like those found in `/etc/rc.d/rc3.d` that in turn start still more processes and services like **xinetd**, **NFS**, and **crond**. As a result, a typical Linux workstation environment may have as many as 50 different processes running before the user even logs in for the first time.

Workstations usually modify system behavior by modifying the contents of `inittab`, or the contents of the subdirectories under `/etc/rc.d`. This capability makes it easy to make large-scale changes to a system's runtime behavior without needing to recompile (or in some cases, even reboot) the system. The conventions followed by `inittab` and `/etc/rc.d` scripts are well documented and pervasive (they predate Linux by a number of years), and lend themselves to automated modification during installation of user software.

To change the final stages of an embedded Linux startup process, you can either provide a modified `inittab` and run **init**, or you can replace **init** entirely, with an application of your own design--- perhaps your embedded application itself. You can even experiment a bit, by providing the names of programs like `/bin/sh` in the kernel's `init=` command line parameter of a Linux workstation. The kernel will simply run the specified program at the end of the boot process, instead of **init**.

[Figure 11](#) shows an excerpt from a typical `inittab` file, that runs the scripts in `/etc/rc.d/rc.sysinit` and `/etc/rc.d/rc3.d`, and launches a few **mingetty**'s to provide login prompts.

```
id:3:initdefault:

# System initialization.
si::sysinit:/etc/rc.d/rc.sysinit

10:0:wait:/etc/rc.d/rc 0
11:1:wait:/etc/rc.d/rc 1
12:2:wait:/etc/rc.d/rc 2
13:3:wait:/etc/rc.d/rc 3
14:4:wait:/etc/rc.d/rc 4
15:5:wait:/etc/rc.d/rc 5
16:6:wait:/etc/rc.d/rc 6

# Things to run in every runlevel.
ud::once:/sbin/update

# Trap CTRL-ALT-DELETE
ca::ctrlaltdel:/sbin/shutdown -t3 -r now

# Run gettys in standard runlevels
1:2345:respawn:/sbin/mingetty tty1
2:2345:respawn:/sbin/mingetty tty2
3:2345:respawn:/sbin/mingetty tty3
4:2345:respawn:/sbin/mingetty tty4
5:2345:respawn:/sbin/mingetty tty5
6:2345:respawn:/sbin/mingetty tty6
```

Figure 11. Excerpt from a typical `inittab`.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

The `mount_root()` Function

Conclusion

[<<<](#)[Previous](#)[Next >>>](#)

Conclusion

Far from the mysterious entity that many claim it is, Linux's boot process is straightforward and easy to follow after spending a few minutes looking at the source code. Knowing Linux's boot process is important, because in embedded settings the generic boot procedure must almost always be modified to meet the needs of the target application. This document should help.

[<<< Previous](#)[Home](#)[Next >>>](#)The `/sbin/init` Program

Copyright

[<<<](#)

[Previous](#)

[Next >>>](#)

Copyright

This article is Copyright (c) 2001 by Bill Gatliff. All rights reserved. Reproduction for personal use is encouraged as long as the document is reproduced in its entirety, including this copyright notice. For other uses, contact the author.

[<<< Previous](#)

[Home](#)

[Next >>>](#)

Conclusion

About the Author

[<<<](#)

[Previous](#)

About the Author

Bill Gatliff is an independent consultant with almost ten years of embedded development and training experience. He specializes GNU-based embedded development, and in using and adapting GNU tools to meet the needs of difficult development problems. He welcomes the opportunity to participate in projects of all types.

Bill is a Contributing Editor for [Embedded Systems Programming Magazine](#), a member of the Advisory Panel for the [Embedded Systems Conference](#), maintainer of the Crossgcc FAQ, creator of the [gdbstubs](#) project, and a noted author and speaker.

Bill welcomes feedback and suggestions. Contact information is on his website, at <http://www.billgatliff.com>.

[<<< Previous](#)

[Home](#)

Copyright